

Crimper **Hose** **Coupling** **Crimp Instructions** **CHART NUMBER** **49** **REV 02**

K16 **111** **9200** **One-Piece** Mark the hose at a distance from the end of the hose equal to the "Insertion Length". Install the fitting on the hose so that the mark is even with the end of the ferrule. Crimp the entire length of the ferrule to the Crimp Diameter given in the table. Tolerance +/- 0.1 mm or +/- 0.004 inches .

Hose	Ferrule	Fitting Insertion Length	Die	Crimp Position	Crimp Length	Crimp Diameter		Dial Setting	
						mm	in	Approx.	Actual
111-04	9200	20	0.600	FLUSH	FULL	16.9	0.665	70	_____
		Alternate	0.500						63
111-06	9200	21	0.750	FLUSH	FULL	20.6	0.811	71	_____
		Alternate							
111-08	9200	26	0.915	FLUSH	FULL	23.7	0.933	76	_____
		Alternate	0.750						61

Crimper **Hose** **Coupling** **Crimp Instructions** **CHART NUMBER** **50** **REV 02**

K16 **122** **9200** **One-Piece** Mark the hose at a distance from the end of the hose equal to the "Insertion Length". Install the fitting on the hose so that the mark is even with the end of the ferrule. Crimp the entire length of the ferrule to the Crimp Diameter given in the table. Tolerance +/- 0.1 mm or +/- 0.004 inches .

Hose	Ferrule	Fitting Insertion Length	Die	Crimp Position	Crimp Length	Crimp Diameter		Dial Setting	
						mm	in	Approx.	Actual
122-04	9200	20	0.600	FLUSH	FULL	17.7	0.697	67	_____
		Alternate	0.500						60
122-06	9200	21	0.750	FLUSH	FULL	21.5	0.846	69	_____
		Alternate							
122-08	9200	25	0.915	FLUSH	FULL	24.6	0.969	73	_____
		Alternate	0.750						59

Crimper Hose Coupling

Crimp Instructions

CHART NUMBER

50

REV 02